Xnightsbridge


DATASHEET



TRLED22

230V IP65 2ft 28W Twin LED Non-Corrosive

www.mlaccessories.co.uk



MLA PART CODE	TRLED22
DESCRIPTION	230V IP65 2ft 28W Twin LED Non-Corrosive
NET WEIGHT (KG)	1.22
FINISH	Grey
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 653 Height - 90 Width - 129
CONSTRUCTION	Construction - Polycarbonate
CLASS	I
IP RATING	IP65
WATTAGE (W)	28
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	3050
LUMENS LIGHT SOURCE ONLY (LM)	3670
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	135.92
CIRCUIT WATTAGE (W)	27.06
ССТ	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.124
DISPLACEMENT FACTOR	>0.9
SVM	0.781
PST-LM	0.038
BEAM ANGLE (DEGREES)	120
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	50,000





Xnightsbridge

DIMMABLE	No
OPERATING TEMPERATURE	-20~35°C
INPUT VOLTAGE	230V 50Hz
CABLE ENTRY (MM)	20
CABLE GLAND INCLUDED	Compression gland
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 21W OUTPUT VOLTAGE - 30-43V OUTPUT CURRENT - 480mA EFFICIENCY FULL LOAD - 89.36% ISOLATION - SELV CASE TEMPERATURE (Tc) - 75°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832971085

Date Created: 14/02/2022 12:28





