

SPECIFICATION SHEET

Product Code CMA110

Description 10AX 1 Gang DP 'Emergency Test' Key Switch



General Information	
Dimensions	146mm x 86mm x 9.5mm
Material composition	Rear Housing: Nylon Front Plate: Urea Terminals: Brass Earth Strap: Mild Steel Terminal Screws: Steel and Yellow Passivated Silver "on-lay" copper/brass contacts.
Back Box Depth	25mm – 47mm
Cable Size	4 x 1.5mm ² or 2 x 2.5mm ²
Terminal Size	Live: 3.5mm
Load Rating	10AX (Suitable for Inductive loads)
Modular	Yes
Gang	1
Double Pole	Yes
Print	Yes 'Emergency Test'
Key Switch	Yes
Warranty	20 Years Domestic

Standards	BS EN 60669
------------------	-------------

Additional Information	
	<p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p> <p>All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.</p> <p>Interchangeable with switches in the Mini Grid system</p> 