

TKE/B 40/RD



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

| | |
|---------------------------------|---------------------------|
| Material cable gland | Brass nickel-plated |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP68 (5 bar 30 min), IP69 |
| Surface | Nickel-plated |
| Thread type | M |
| Ø Connection thread D | 40 |
| Lead | 1,5 |
| Length screw-in thread L | 8 mm |
| Key width SW | 46 mm |
| Total length TL | 44 mm - 55 mm |
| Type of cable anchorage | A |
| Install. torques fitting | 20 N/m |
| Install. torques cap nut | 20 N/m |
| Impact category | 6 |
| Order no. nickel-plated | 10106235 |
| Type | TKE/B 40/RD |
| Packing unit | 1 |
| ETIM-Classification | EC000441 |

Description:

UNIVERSAL OPTION Suitable for 32 or 40 mm. IP 68 Brass cable gland. EMSKV 40/ MFD 2 x 11 mm Tails and 1 x 6 mm Earth. Kit contains insert, locknut, blanking insert and MEM reduce.

25.08.2020

Your Contact:

WISKA UK Ltd.

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk