

STRIP AND DRIVER KIT IP33 5M 3000K 12V 6W/M 425LM/M 60LED/M 8MM WIDTH 115 BEAM BOX PACK WITH 12V IP20 50W DRIVER INTEGRAL

ILSTWHIA062W



This Integral LED 5M Strip and Driver Kit combines our 5 meter IP33 warm white LED strip and 40W 12V constant voltage LED driver. Integral LED warm white LED strip has 60 LEDs per metre and is constructed using high quality materials to ensure a consistent light and colour across the strip. This LED strip is IP33 rated and is suitable for indoor applications. Each 5m reel is supplied with an easy-to-follow installation guide and an extra connector to power the strip if it is cut into two lengths. Additional accessories are available, to suit specific installation requirements. The kit also contains Integral LED 40W 12V constant voltage LED driver operates 200-240VAC input range. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

Details

Quick Order Code:	33632
Barcode:	5055788227885
Category:	Strips
Range Name:	Strip And Driver Kit
Product Type:	White strip
Warranty (Years):	3
CE RoHS:	Yes

Physical Data

Product Width (mm):	8
Product Weight (g):	252
Material:	Strip: PCB, Driver: Plastic Shell
Construction:	LED surface mounted on to strip
Strip Cut Points (mm):	50
Max Run Length (m):	5
Strip length (M):	5
Strip Width (mm):	8

Electrical Data

Power Consumption per meter (W/m):	6
Voltage (V):	12
Watts per metre:	3.1W - 6w
Dimming:	Dimmable

Driver Included:	Yes
Electric Current:	AC
Protection Function:	Short Circuit, overload and overheating protection on driver
LVD Certified:	Yes

Light Data

Luminous efficacy (lm/W):	50
Lumens per meter (lm/m):	425
Correlated Colour Temperature (CCT) (K):	3000
Colour Temperature Name:	Warm White
Beam Angle:	115
Colour Rendering Index (CRI):	80
Colour Type:	White
LED Size (mm):	3528
LED Type:	Surface mounted device (SMD)
LEDs per meter:	60
Lifetime (hours):	13000
Reel Length (m):	5

Environment

LVD Certified:	Yes
CE RoHS:	Yes
Lowest Operating Temperature (°C):	-20
Maximum Operating Temperature (°C):	45

Packaging

Package Weight (g):	420
Package Length (mm):	355
Package Width (mm):	220
Package Depth (mm):	40