

Robustly constructed & suitable for multiple commercial use where performance and functionality are required.

PERFECT FOR MULTI-PURPOSE COMMERCIAL APPLICATIONS

Download IES File from website

Photocell

20mm knockouts

Captive stainless steel screws

LED LAMP SPECIFICATIONS:

Lumens total flux	2000 lm
Rated Wattage	30W
Rated luminous flux	2000 lm
Nominal life time of the lamp	30,000 hrs
Colour temperature	4200K
Number of switching cycles before premature lamp failure	≥15,000
Warm-up time up to 60 % of the full light output	Instant full light
Dimmable	No
LED array dimensions (W/H)	198 x 167mm
Nominal beam angle	120°
Rated power	30W
Rated lamp lifetime	30,000 hrs
Displacement factor	
Lumen maintenance factor at end of nominal life	≥0.70
Starting time	<0.1s
Colour rendering	≥80
Colour consistency	Within 6 step Macadam ellipse
Rated peak intensity	720cd
Rated beam angle	120°
Voltage	220/240V


This product contains a Light Source of Energy Efficiency Class G

Not suitable for accent lighting

Eterna[®]
Everyday Lighting For Professionals

30W INTEGRATED LED BULKHEAD

- Captive stainless steel screws
- 20mm knockouts side and rear
- **WPACKLEDPC**: photocell for dusk to dawn operation
- Tough polycarbonate housing
- IK08
- 5 year warranty



• M.O.M: 1 / O.P.Q: 4

Code	Version	Colour	Wattage	Colour Temp.	Lumens	Avg. Rated Life (Hrs)	IP Rating
WPACKLED	Standard	Black	30W	4200K	2000 lm	30,000 hrs	IP65
WPACKLEDPC	Photocell						