

It is the responsibility of the person installing the electrical equipment to ensure that the installation meets the requirements of the IET wiring regulations and is therefore 'fit for purpose'. Factors such as correct selection of components, cable sizing, protective devices and Earth bonding are all critical and should be checked prior to full testing and power-up. Any other regulations applicable to the equipment being installed such as the Machinery Directive and current health and safety legislation must also be adhered to.

All connections (including factory made) must be checked for the correct tightness prior to commissioning of the electrical installation. All connections should be inspected periodically to ensure correct tightness.

DO NOT USE POWER TOOLS ON THESE PRODUCTS

Europa Helpline: 01582 692 444 / **Email:** technical@europacomponents.com

Europa House, Airport Way, Luton, Beds, LU2 9NH Tel: 01582 692 440

e-mail: sales@europacomponents.com website: www.europacomponents.com



IP65 / IP67 SWITCHED INTERLOCKED SOCKETS WITH RCD PROTECTION

Features & Benefits

- IP65 Enclosure | IP67 Socket
- Complete with pre-fitted 30mA Type A RCCB
- RCCB conforms to BS EN 61008, RCBO conforms to BS EN 61009, Interlocked Socket conforms to IEC EN 60309-2
- Self-extinguishing – manufactured in fire & shock resistant material.
- Unique aluminium key – once removed the control lever can no longer be activated.
- Includes spirit level to make installation easier.
- Four cable inlets M25 / M32 top, bottom and side entry.

Part Number	RCCB	No. of Poles	Amps	Voltage
SISRAW163P	25A 30mA 2P Type A	2P+E	16A	230V
SISRAW323P	40A 30mA 2P Type A	2P+E	32A	230V
SISRAW164V	25A 30mA 3P Type A	3P+E	16A	415V
SISRAW324V	40A 30mA 3P Type A	3P+E	32A	415V
SISRAW165V	25A 30mA 4P Type A	3P+N+E	16A	415V
SISRAW325V	40A 30mA 4P Type A	3P+N+E	32A	415V

Width: 105mm



Height: 335mm

Depth Including Switch:
16A 145mm
32A 155mm