

**STRIP AND DRIVER KIT IP20 5M 4000K 12V 6W/M 460LM/M 60LED/M 8MM WIDTH 115 BEAM BOX PACK WITH 12V IP20 50W DRIVER INTEGRAL**

ILSTWHIA125W



Integral LED 5M Strip and Driver Kit comprises of our 5 meter IP20 cool white LED strip and 40W 12V constant voltage LED driver. Integral LED cool white LED strip has 60 LEDs per metre and is constructed using high quality materials to ensure a consistent light and colour across the strip. This LED strip is IP20 rated and is suitable for indoor applications. Each 5m reel is supplied with an easy-to-follow installation guide and an extra connector to power the strip if it is cut into two lengths. Additional accessories are available, to suit specific installation requirements. The kit also contains Integral LED 40W 12V constant voltage LED driver operates 200-240VAC input range. The LED driver features an ultra slim, IP20 rated casing that helps to provide an easy installation and smart finish, ideal for indoor use.

**Details**

<b>Quick Order Code:</b>	765787
<b>Barcode:</b>	5055788246923
<b>Category:</b>	Strips
<b>Range Name:</b>	Strip And Driver Kit
<b>Product Type:</b>	White strip
<b>Market Segment:</b>	Decorative indoor
<b>Warranty (Years):</b>	3
<b>CE RoHS:</b>	Yes

**Physical Data**

<b>Product Width (mm):</b>	8
<b>Product Weight (g):</b>	252
<b>Material:</b>	Strip: PCB, Driver: Plastic Shell
<b>Construction:</b>	LED surface mounted on to strip
<b>Strip Cut Points (mm):</b>	50
<b>Max Run Length (m):</b>	5
<b>Placement / Application:</b>	Decorative indoor
<b>Strip length (M):</b>	5
<b>Strip Width (mm):</b>	8

**Electrical Data**

<b>Power Consumption per meter (W/m):</b>	6
<b>Voltage (V):</b>	12

<b>Watts per metre:</b>	3.1W - 6w
<b>Dimming:</b>	Dimmable
<b>Driver Included:</b>	Yes
<b>Electric Current:</b>	AC
<b>Protection Function:</b>	Short Circuit, overload and overheating protection on driver
<b>LVD Certified:</b>	Yes

## Light Data

<b>Lumens per meter (lm/m):</b>	460
<b>Correlated Colour Temperature (CCT) (K):</b>	4000
<b>Colour Temperature Name:</b>	Cool White
<b>Beam Angle:</b>	115
<b>Colour Rendering Index (CRI):</b>	90
<b>Colour Type:</b>	White
<b>LED Size (mm):</b>	2835
<b>LED Type:</b>	Surface mounted device (SMD)
<b>LEDs per meter:</b>	60
<b>Lifetime (hours):</b>	25000
<b>Reel Length (m):</b>	5

## Environment

<b>LVD Certified:</b>	Yes
<b>CE RoHS:</b>	Yes
<b>Lowest Operating Temperature (°C):</b>	-20
<b>Maximum Operating Temperature (°C):</b>	45

## Packaging

<b>Package Weight (g):</b>	420
<b>Package Length (mm):</b>	355
<b>Package Width (mm):</b>	220
<b>Package Depth (mm):</b>	40