



Category	Bulkheads
Application	Commercial, Industrial, Outdoor
Specification	Performance

Sleek

Sleek Bulkhead 2CCT Multi Wattage Photocell

Code: ASLE/1/PC



PRODUCT FEATURES

- All polycarbonate multi-purpose bulkhead suitable for external commercial applications
- CCT selectable between 3000K and 4000K
- Non-dimmable
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching

GENERAL INFORMATION

Wattage	5W - 8W
Lumens Delivered	570lm - 960lm (4000K)
Lm/W	114lm/W - 119lm/W (4000K)
Beam Angle	120
CRI	80
CCT	3000/4000K
Input	220/240V
Operating Temp	-10°C - 40°C
SDCM	6
Product Weight without Packaging	0.4 kg

TECHNICAL INFORMATION

Light Source	LED
Colour / Finish	Black
IP Rating	IP65
Class Protection	2
Internal / External	Internal / External
Surface / Recessed / Suspended	Ceiling, Wall
Lumen Depreciation	L70 >54,000h
Warranty (Years)	5
CE Mark	Yes
Height	76 mm



Category	Bulkheads
Application	Commercial, Industrial, Outdoor
Specification	Performance

Sleek

Sleek Bulkhead 2CCT Multi Wattage Photocell
Code: ASLE/1/PC

