For general, industrial and commercial application

Lamp Options

T5: 16mm Fluorescent Tubes T8: 26mm Fluorescent Tubes

T12: 38mm Fluorescent Tubes

A wide range of high quality British made

Attractively designed single lamp batten luminaire specifically for T5 and T8 lamps.



Applications:

FL FITZGERALD

LIGHTPACK TO

- Schools
- Offices
- Kitchens
- Workshops
- Corridors

battens, all supplied with lamps.

14/24W ONLY 58W T5 LIGHTPACK T8 LIGHTPACK

Designed and manufactured to comply with EN 60598 and are CE certified.

Product Specification

- Supplied with colour 840 lamps
- · Manufactured from mild steel
- · Resilient white finish
- · Polycarbonate lampholders

Optional Features (Add suffix to order code)

/FTB: Fused terminal block

Optional Lamp Type (Add suffix to order code)

/X: Supplied excluding lamps

/865: Supplied with colour 865 lamps

For Accessories please see pages 44-49

Order Codes

Including Lamps

T5 Tube - HF as standard

Order Code	Watt	Α	В	C	Kg
LP114/HF/840**	1 x 14	574	330	-	2.4
LP121/HF/840**	1 x 21	874	630	300	2.4
LP124/HF/840**	1 x 24	574	330	-	2.4
LP128/HF/840	1 x 28	1174	930	600	2.4
LP135/HF/840	1 x 35	1474	1230	600	2.4
LP139/HF/840	1 x 39	874	630	300	2.4
LP149/HF/840	1 x 49	1474	1230	600	2.4
LP154/HF/840	1 x 54	1174	930	600	2.4
I D190/UE/9/0	1 v 90	1/17/	1220	600	2.4

TR Tube - SS as standard

Order Code	Watt	Α	В	С	Kg
LP118/840**	1 x 18	612	-	-	1.3
LP130/840**	1 x 30	917	-	-	1.4
LP136/840**	1 x 36	1221	966	600	1.5
LP158/840	1 x 58	1521	1266	600	1.9
LP170/840	1 x 70	1784	1530	600	2.3

T8 Tube - Low Power Factor only

Order Code	Watt	Α	В	С	Kg
LPF118/840*	1 x 18	612	-	-	1.3
LPF130/840*	1 x 30	917	-	-	1.4
LPF136/840*	1 x 36	1221	966	600	1.5
LPF158/840*	1 x 58	1521	1266	600	1.9

T12 Tube - SS only

Order Code	Watt	Α	В	C	Kg
LP1100/840*	1 x 100	2394	2140	1200	4.9

- * Not available with an emergency option.
- ** Only available with remote emergency.

Gear options

/HF: High Frequency /AD: 1-10V Analogue Dimming

/SD: Retractive Switch Dimming /DD: DSI Digital Dimming

/DL: DALI Addressable Dimming

Emergency options

/M3: 3hr Maintained Emergency /RM3: Remote Maintained Emergency /LS3: LED 3hr Sustained Emergency

Lightpack Part Code Formula:

Product Number Family of Lamps Option



Installation	
Exposed T	×
Plasterboard	×
Metal Pan	×
Surface	~
Suspended	

ENERGY SAVINGS

We have a range of lighting controls that can offer motion and daylight sensing. This intelligence can either be integral to the fitting or located remotely. For more information and a free 'Return On Investment' report, your local Fitzgerald contact would be delighted to assist.